















Lampentabelle – Leuchtstofflampen

Lampentyp/Lampensockel	Socket	Leistung (W)	max. Länge C (mm) nach IEC	
TC-DEL 	G24q-1	10 13	95 130	
	G24q-2	18	140	
	G24q-3	26	160	
TC-TEL 	GX24q-1	13	90	
	GX24q-2	18	110	
	GX24q-3	26	130	
		32	145	
	GX24q-4	42	155	
	GX24q-5	57	181 *	
TC-D 	G24d-1	8	73 *	
		10	95	
		13	130	
	G24d-2	18	140	
TC-T 	GX24d-1	13	90	
	GX24d-2	18	110	
	GX24d-3	26	130	
TC-S 	G23	5	85	
		7	115	
		9	145	
		11	215	
TC-SEL 	2G7	5	85	
		7	115	
		9	145	
		11	215	
TC-TEL 	2G8-1	60	167 *	
		85	208 *	
		120	285 *	
TC-DD 			A	B
	GR8	16	138	141
		28	205	207
	GR10q	10	92	95
		16	138	141
		21	138	141
		28	205	207
		38	205	207
	GRY10q-3	55	205	205 *
	GRZ10d	18	137	141
	GRZ10t	30	202	206
TC-F 	2G10	18	122	
		24	165	
		36	217	
TC-L 	2G11	18	225	
		24	320	
		34	533 *	
		36	415	
		40	535	
		55	535	
		80	565	
	GX53-1	7		






Lampentabelle – Leuchtstofflampen

Lampentyp/Lampensockel	Socket	Leistung (W)	Ø D (mm)	Länge A/C (mm) nach IEC 60081/ 60901 (bei Ringlampen B)
T2 (T7)  W4.3	W4.3x8.5d	6	7	219,3
		8	7	320,9
		11	7	422,5
		13	7	524,1
T5 (T16)  G5	G5	4	16	135,9
		6	16	212,1
		8	16	288,3
		13	16	516,9
		14	16	549,0
		21	16	849,0
		24	16	549,0
		28	16	1149,0
		35	16	1449,0
		39	16	849,0
		49	16	1449,0
		54	16	1149,0
		80	16	1449,0
T8 (T26)  G13	G13	10	26	470,0 ^{*2}
		14	26	360,0 ^{*2}
		15	26	437,4
		16	26	589,8
		16	26	720,0 ^{*2}
		18	26	589,8
		20 ^{*1}	26	438,0
		20	26	589,8
		23	26	970,0
		30	26	894,6
		32	26	1199,4
		33	26	1149,0
		34	26	1047,0
		36	26	1199,4
		36	26	970,0 ^{*2}
		38	26	1047,0
		50	26	1500,0
		58	26	1500,0
		70	26	1763,8
T12 (T38)  G13	G13	20	38	589,8
		25	38	970,0
		30	38	894,6
		40	38	1199,4
		65	38	1500,0
		75	38	1763,8
		80 ^{*1}	38	1500,0
		85	38	2374,3
		85 ^{*1}	38	1763,8
		100	38	2374,3
		100 ^{*1}	38	1800,0
		115	38	1200,0
		125	38	2374,3
		140	38	1500,0
		140 ^{*1}	38	1800,0
		160 ^{*1}	38	1800,0
T12 (HO)  R17d	R17d	60	38	900,0
		60	38	1166,0
		87	38	1775,6
		112	38	2385,2
		110	38	2400,0
		195	38	2385,0
		215	38	2400,0
		110	54	1200,0
		165	54	1800,0
		215	54	2400,0

Längen für Kunststoff- oder Glasschutzhöhre

Ø D (mm)	Länge L (mm)
38±0,5	L = A - 20±1
50±0,8	L = A - 30±1

Lampentabelle – Leuchtstofflampen

Lampentyp/Lampensockel	Sockel	Leistung (W)	Ø D (mm)	A (mm)
	2GX13	22 40 55 60	16 16 16 16	230,0 * 305,0 * 305,0 * 379,0 *
	G10q	22 32 40 60	28 30 30 30	215,9 311,2 412,8 408,8
	2G13-92	18 36 58	26 26 26	304 * 566, 601 * 566, 759 *

* noch nicht in IEC genormt

